

## **OS-20, Orbital Shaker**





Platform Bio PP-4



Platform UP-12



**OS-20** Orbital Shaker is a powerful variable speed shaker which provides efficient orbital motion. Speed and time are under microprocessor control. Two operation modes are available: 1) **timed** (1–999 min) and 2) **nonstop**, with a maximum operation time of 24 hours.

Five (5) different interchangeable platforms expand possibilities of shaker application in laboratories of different areas: microbiology, chemistry, immunology, biochemistry and molecular biology. Amplitude of 20 mm of the platform shift provides uniform mixing of liquids in flat microtest plates during fulfilment of diagnostic tests, such as VDRL-test.

Shaker can be used in cold rooms or incubators, operating at ambient temperature range  $+4^{\circ}$ C to  $+40^{\circ}$ C. Low voltage external power supply (12 V) provides electrical safety in humid environment.

Specifications:	
Speed range	50-250 rpm
Digital speed control	
Orbit diameter	20 mm
Digital timer	1–999 min
Display	LED
Maximum load	2.5 kg
Overall dimensions (W $\times$ D $\times$ H)	270×260×80 mm
Weight, not more	3.4 kg
Input current/power consumption	12V, 500 mA / 6 W
External power supply Input AC	100-240 V 50/60Hz; Output DC 12V

Catalogue number:	
OS-20 without platform	BS-010108-AAG
UP-12	BS-010108-AK
Bio PP-4	BS-010116-AK
P-6/250	BS-010108-DK
P-12/100	BS-010108-EK
P-16/88	BS-010116-BK

## Platform P-6/250



Description and pictures of all platforms can be found on the next page

## Platforms for OS-20, PSU-10i and ES-20



Platform	Description	Dimensions	Working Dimensions	Used on	Cat. Number
<b>1</b> UP-12	Universal platform with adjustable bars for different types of flasks	285 × 215 mm	265 × 185 mm	OS-20, PSU-10i, ES-20	BS-010108-AK
2 Bio PP-4	Flat platform with non-slip rubber mat	260 × 260 mm	235 × 235 mm	OS-20, PSU-10i	BS-010116-AK
<b>3</b> PP-4	Metallic flat platform with non-slip rubber	220 × 220 mm	215×215 mm	ES-20	BS-010108-BK
<b>4</b> P-12/100	Platform with clamps for flasks, 100–150 ml (12 places)	250 × 190 mm	250 × 190 mm	OS-20, PSU-10i, ES-20	BS-010108-EK
<b>5</b> P-6/250	Platform with clamps for flasks, 250–300 ml (6 places)	250 × 190 mm	250 × 190 mm	OS-20, PSU-10i, ES-20	BS-010108-DK
<b>6</b> P-16/88	Platform with spring holders for up to 88 tubes up to 30 mm diameter (e. g. 10 ml, 15 ml, 50 ml tubes)	275×205×75 mm	275×205×75 mm	OS-20, PSU-10i, ES-20	BS-010116-BK











**4** P-12/100



**6** P-6/250



**6** P-16/88

