Ultra Flat Magnetic Stirrer

Ultra flat, ultra modern!

The Ultra Flat Magnetic Stirrer has no moving mechanical components, so it's maintenance free!

The stirring system, adjustable by means of a microprocessor, is made up of coils that induce a rotating magnetic field. The modern, ergonomic structure is made of materials that guarantee high resistance to the aggression of chemical reagents.

CE*

Features

- Microprocessor controlled
- Gentle start-up offers optimum progression of the stirring speed
- Maintenance free
- Made from chemically resistant materials

Specifications	
Stirring Speed:	Up to 1100 rpm
Stirring Volume:	Up to 5 l (H_2O)
Operating Temperature:	-10 °C to 60 °C
Unit Material:	Technopolymer
Power:	5 W
Power Supply:	100 V – 240 V , 50 – 60 Hz
Weight:	0.9 kg
Dimensions:	160 x 230 x 33 mm

Ultra Flat Magnetic Stirrer		
Cat. No.	Description	Pack Size
N2400-2000	Magnetic Stirrer, ESP, Ultra Flat	1

Magnetic Stirrer with Heater

Stir up some heat!

The Magnetic Stirrer with Heating is equipped with an advanced, electronic speed control.

The stirrer's heating plate is made of aluminium alloy and has a special protective coating that ensures an even heat distribution across the entire surface, as well as providing excellent chemical resistance.

CE*

Features

- Electronic speed control
- Even heat distribution
- Made from chemically resistant materials

Specifications	
Stirring Speed:	Up to 1200 rpm
Stirring Volume:	Up to 15 l (H_2O)
Stirring System:	High-power driving magnet type 'PCM' operated by monophase motor for continuous operation
Programmable Temp. Range:	50 °C to 370 °C
Temperature Regulation:	Room temp. to 370 °C
Unit Material:	Epoxy painted aluminium
Power:	630 W
Power Supply:	230 V / 50 Hz
Weight:	2.9 kg
Heating Plate:	155 mm Ø
Dimensions:	165 x 280 x 115 mm

Magnetic Stirrer with Heater		
Cat. No.	Description	Pack Size
N2400-3000	Magnetic Stirrer with Heater	1

*For detailed information see user manual on our website.